



NOTE
 1. Proximity Sensor는 Option 사양임.
 2. Arm에 조립되는 Roller는 cylindrical type이 기본 사양임.

SPECIFICATION	
CENTERING RANGE	φ4~φ52 mm
PISTON AREA	7 cm²
OPERATING PRESURE	6~50 kgf/cm²
MAX. CLAMPING FORCE/ROLLER	100 kgf
CENTERING ACCURACY WITHIN THE WHOLE RANGE	0.02 mm
REPEATABILITY ACCURACY	0.005 mm
MAX. ROLLER SURFACE SPEED	800 m/min
MASS APPROX	6 kg

* Option of central oil lubrication
 - Oil : ISO VG68
 - For heavy working conditions and high build up of swarf
 - Lubrication intervals 2 ~ 5 min
 - Operating pressure Min.10 bar, Max.40 bar
 - The use of our separate complete lubrication unit with timer control is recommended

NO.	TITLE OF ITEM	MATERIAL	SIZE & SPEC.	QTY	NOTE
01	ASSY	STD	STRA-1	1SET	-
TITLE		STEADY REST (STRA-1)		PART NAME	ASSEMBLY DRAWING
DWG. NO.		STRA-1		AGENCY	
CODE NO.		-		USER	
SCALE		1 : 1		DATE	
APPROVED		Checked	Designed		

