

[ MTR2-15420FF Specifications ]

A축 사양 (경사)		C축 사양 (회전)	
Tilting Angle	-20° ~ +120°	Rotating Angle	360°
Clamp Force	- N.m	CLAMP FORCE	- N.m
Clamp Pressure	21 ~ 25 kgf/cm <sup>2</sup>	Clamp Pressure	21 ~ 25 kgf/cm <sup>2</sup>
Gear Ratio	1 / 120	Gear Ratio	1 / 120
Max. RPM	25 (Motor 3000 min <sup>-1</sup> )	Max. RPM	25 (Motor 3000 min <sup>-1</sup> )
Servo Motor	a4 / 4000i	Servo Motor	a4 / 4000i

Work Weight ( kgf )  
 Left Axis : -  
 Right Axis : -

Weight : ~ kgf ( 유압 배관 제외 )

[ Rotary Joint Specifications ]

"A" 축 사양 (경사)		"C" 축 사양 (회전)	
Temperature	MAX. 80°C	Temperature	MAX. 80°C
Hydraulic	MAX. 150 kgf/cm <sup>2</sup>	Hydraulic	MAX. 150 kgf/cm <sup>2</sup>
RPM	MAX. 80 RPM	RPM	MAX. 100 RPM
PORT	7 PORT	PORT	각 5 PORT

